

# AUSFLOW

## Airseeders

### Towed Between

	A95002BT	A110003BT
Total Tank Capacity (Lt)	9400	10900
Front Tank Capacity (Lt)	4700	4700
Second Tank Capacity (Lt)	4700	1500
Third Tank Capacity (Lt)	N/A	4700
Fourth Tank Capacity (Lt)	N/A	N/A
Fifth Tank Capacity (Lt)	N/A	N/A
Front Axle	N/A	N/A
Front Tyres	N/A	N/A
Rear Tyres	24.5x32	24.5x32
Drawbar Weight - empty (Kg)	700	800
Drawbar Weight - full (Kg)	2400	2900
Length	8200	8800
Width	3500	3500
Height	3800	3800
Auger	8"	8"

### Notes for Airseeders

All Machines include augers, hydraulic oil heat exchangers and full flow hydraulic filter with service indicator

Variable rate standard on all models

3 metre track option available on (TBH) Tow Behind models

Staggered axle option available on (TBH) Tow Behind models

Choice of Topcon Eagle and X20 or Cambut controller suitable for Trimble FM 1000 monitor upto 4 tanks

Specifications and dimensions are nominal and subject to change without notice or obligation

Quoted tank volumes are nominal and subject to manufacturing tolerances

\*Towed behind Airseeders are not suitable for DBS Auseeders D260-70 and 'W' series

Quoted weights are approximate and subject to product densities and % bin fill

Quoted weights include small seeds (SG 0.7), seed (SG 0.8), fertiliser (SG 1.0) and 1 x liquid on Multistream's (SG 1.32)