

# AUSFLOW

## D Series

	D260-24	D260-32	D260-36	D260-42	D260-48N	D260-48E	D260-54	D260-59	D260-64	D260-70*
Dig Width (metres)	6.24	8.32	9.36	10.92	12.48	12.48	14.04	15.34	16.64	18.20
Dig Width (feet)	20' 06"	27' 04"	30' 09"	35' 10"	40'11"	40'11"	46' 01"	50' 04"	54' 07"	59' 09"
Number of tines	24	32	36	42	48	48	54	59	64	70
Tine spacing (mm)	260	260	260	260	260	260	260	260	260	260
Tine spacing (inches)	10	10	10	10	10	10	10	10	10	10
Number of rows	3	3	3	3	3	3	3	3	3	3
Underframe clearance (mm)	730	730	730	730	730	730	730	730	730	730
Transport width (metres)	6.40	5.86	5.86	5.86	5.86	7.42	7.42	6.75	7.42	7.53
Transport width (feet)	21' 00"	19' 03"	19' 03"	19' 03"	19' 03"	24' 04"	24' 04"	22' 02"	24' 04"	24' 09"
Transport height (metres)	N/A	3.31	3.83	4.61	5.36	4.61	5.36	5.03	5.03	5.82
Transport height (feet)	N/A	10' 11"	12' 07"	15' 02"	17' 07"	15' 02"	17' 07"	16' 06"	16' 06"	19' 01"
Recommended Engine power (Kw)	125	167	188	219	251	251	282	308	334	366
Recommended Engine power (Hp)	168	224	252	294	336	336	378	413	448	490
Max work depth (mm)	230	230	230	230	230	230	230	230	230	230
Number of wheels	4	6	6	6 or 8	8	6 or 8	8	10	10	10
Tyres	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5
Frame sections	1	3	3	3	3	3	3	5	5	5
Frame tilt modules	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Weight on drawbar - working (Kg)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Weight on drawbar - transport (Kg)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Approximate weight base (Kg)	4500	7000	7500	8300	9000	9000	9700	11800	12400	13050
Hose and liquid kit weight (Kg)	500	600	650	700	800	750	900	950	1000	1050
Coulter weight (Kg)	650	850	950	1150	1300	1300	1450	1600	1800	1900
Total maximum weight (Kg) (Approx)	5650	8450	9100	10150	11100	11050	12050	14350	15200	16000

### Notes for DBS Auseders

- **Horsepower should not exceed 6Kw (8hp) per tine**
- Tine Type: Hydraulic edge-on high breakout cushion return
- Engine power required is approximately 5 - 8 hp (3.7 - 6.0Kw) per tine depending on soil type and blade length
- Specifications are nominal and subject to change
- Dimensions, weight and power requirements are nominal and based on machines with standard 175mm (7") blades
- Transport height and width may exceed local limits and all machines towed at owners's risk
- \* Towed behind Multistream and Airseeders not suitable for DBS Auseder D260-70 and 'W' Series
- \*\* 'W' Series estimate