



**D Series**

	D300-32	D300-36	D300-40	D300-44	D300-46	D300-47	D300-48	D300-49	D300-51	D300-55	D300-61
Dig Width (metres)	9.60	10.80	12.00	13.20	13.80	14.10	14.40	14.70	15.30	16.50	18.30
Dig Width (feet)	31' 06"	35' 05"	39' 05"	43' 04"	45' 03"	46' 03"	47' 03"	48' 03"	50' 02"	54' 02"	60' 00"
Number of tines	32	36	40	44	46	47	48	49	51	55	61
Tine spacing (mm)	300	300	300	300	300	300	300	300	300	300	300
Tine spacing (inches)	12	12	12	12	12	12	12	12	12	12	12
Number of rows	3	3	3	3	3	3	3	3	3	3	3
Underframe clearance (mm)	730	730	730	730	730	730	730	730	730	730	730
Transport width (metres)	6.50	6.50	6.50	6.50	6.50	7.37	6.50	7.37	7.37	7.96	7.96
Transport width (feet)	21' 04"	21' 04"	21' 04"	21' 04"	21' 04"	24' 02"	21' 04"	24' 02"	24' 02"	26' 01"	26' 01"
Transport height (metres)	3.57	4.17	4.63	5.4	5.53	5.3	6.00	5.53	5.90	4.69	5.59
Transport height (feet)	11' 09"	13' 08"	15' 03"	17' 09"	18' 04"	17' 05"	19' 09"	18' 04"	19' 05"	15' 05"	18' 04"
Recommended Engine power (Kw)	167	188	209	230	240	245	251	256	266	287	319
Recommended Engine power (Hp)	224	252	280	308	322	329	336	343	357	385	427
Max work depth (mm)	230	230	230	230	230	230	230	230	230	230	230
Number of wheels	6	6	6 or 8	8	8	8	8	8	8	8	10
Tyres	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5
Frame sections	3	3	3	3	3	3	3	3	3	5	5
Frame tilt modules	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Weight on drawbar - working (Kg)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Weight on drawbar - transport (Kg)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Approximate weight base (Kg)	7100	7700	8400	8900	9100	9400	9400	9550	9700	11300	12300
Hose and liquid kit weight (Kg)	600	650	700	750	800	800	850	850	900	950	1000
Coulters weight (Kg)	900	1000	1150	1250	1300	1300	1350	1400	1450	1600	1750
Total maximum weight (Kg) (Approx)	8600	9350	10250	10900	11200	11500	11600	11800	12050	13850	15050

**Notes for DBS Auseeders**

- **Horsepower should not exceed 6Kw (8hp) per tine**
- Tine Type: Hydraulic edge-on high breakout cushion return
- Engine power required is approximately 5 - 8 hp (3.7 - 6.0Kw) per tine depending on soil type and blade length
- Specifications are nominal and subject to change
- Dimensions, weight and power requirements are nominal and based on machines with standard 175mm (7") blades
- Transport height and width may exceed local limits and all machines towed at owners's risk
- \* Towed behind Multistream and Airseeders not suitable for DBS Ausseeder D260-70 and 'W' Series
- \*\* 'W' Series estimate