

AUSPLOW

	E520-5	Easitill II E520-23
Dig Width (metres)	2.60	11.96
Dig Width (feet)	8' 06"	39'03"
Number of tines	5	23
Tine spacing (mm)	520	520
Tine spacing (inches)	20"	20"
Number of rows	3	3
Underframe clearance (mm)	750	750
Transport width (metres)	2.27	6.96**
Transport width (feet)	7' 06"	22' 10"***
Transport height (metres)	N/A	4.58**
Transport height (feet)	N/A	15' 01"***
Recommended Engine power (Kw)	50	230
Recommended Engine power (Hp)	67	308
Max work depth 750mm shank (mm)	300	300
Max work depth 750mm shank (inches)	12"	12"
Max work depth 820mm shank (mm)	380	380
Max work depth 820mm (inches)	15"	15"
Shank jump height (mm)	490	490
Shank jump height (inches)	19"	19"
Shank width (mm)	20	20
Frame sections	1	3
Tine breakout force (Kg)*	650	650
Tine breakout force (lbs)*	1430	1430
Number of wheels	2	4
Tyres	7.5-16	386x65R 22.5

Notes for Easitill II

- Maximum allowable horsepower per tine - 12Kw (16hp)
- *Tine breakout force at 100 Bar (1450 psi)
- Optional 820mm (32 1/4") shank - sand plain use **only**
- Specifications and dimensions are nominal and subject to change without notice or obligation
- **Estimated