

AUSFLOW

Multistream

Towed Between

	M90003BT	M120004BT	M140003BT	M150004BT	M180004BT	M195005BT	M220005BT	M240006BT	M270006BT	M280007BT
Total Tank Capacity (Lt)	9000	12000	13800	15300	18200	19700	22600	24100	27000	28500
Front Tank Capacity (Lt)	3000	3000	4700	4700	4700	4700	4700	4700	4700	4700
Second Tank Capacity (Lt)	3000	3000	4400	1500	4400	4400	4400	4400	4400	4400
Third Tank Capacity (Lt)	3000	3000	4700	4400	4400	1500	4400	1500	4400	1500
Fourth Tank Capacity (Lt)	N/A	3000	N/A	4700	4700	4400	4400	4400	4400	4400
Fifth Tank Capacity (Lt)	N/A	N/A	N/A	N/A	N/A	4700	4700	4400	4400	4400
Sixth Tank Capacity (Lt)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	4700	4700	4400
Seventh Tank Capacity (Lt)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	4700
Front Axle	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Front Tyres	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Rear Tyres	24.5x32	30.5x32	30.5x32	30.5x32	24.5x32 Duals	24.5x32 Duals	710/70R 38 Duals	710/70R 38 Duals	800/70R 38 Duals	800/70R 38 Duals
Drawbar Weight - empty (Kg)**	1000	1500	1100	1200	1100	1200	900	1000	1500	1600
Drawbar Weight - full (Kg)**	3300	4900	4800	5300	3800	4300	1800	2300	4200	4700
Length (mm)	8500	9700	8500	9100	10300	10900	10700	11300	12000	12600
Width (mm)	3300	3500	3500	3500	4700	4700	5500	5500	5600	5600
Height (mm)	3400	3400	3800	3800	3800	3800	3900	3900	3900	3900
Auger	8"	8"	10"	10"	10"	10"	10"	10"	10"	10"
Engine Option Available	N/A	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Notes for Multistreams

- All Machines include augers, hydraulic oil heat exchangers and full flow hydraulic filter with service indicator
- Variable rate standard on all models
- 3 metre track option available on (TBH) Tow Behind models
- Staggered axle option available on (TBH) Tow Behind models
- Choice of Topcon Eagle and X20 or Cambut controller suitable for Trimble FM 1000 monitor upto 4 tanks
- All tanks can be fitted with optional liquid delivery systems
- Specifications and dimensions are nominal and subject to change without notice or obligation
- Quoted tank volumes are nominal and subject to manufacturing tolerances
- *Towed behind Multistreams are not suitable for DBS Auseeders D260-70 and 'W' series
- Quoted weights are approximate and subject to product densities and % bin fill
- Quoted weights includes, small seed (SG 0.7), seed (SG 0.8), fertiliser (SG 1.0) and 1 x liquid on Multistream's (SG 1.32)
- **With engine option add 400Kg to the drawbar weights